



SPECIFICATION DATA SHEET 11.2

Hybrid Mounting Bolts



3/8" Bolt Key #21HKHKA



3/8" Bolt Bit #21HKHB



Hybrid Mounting Bolts

Hex Head Mounting Bolts

Stainless steel (18-8), hex head mounting bolts are available. Hex head mounting bolts will be supplied when the letter "M" is shown in column thirteen of the interlock part number. Reference the Hybrid Ordering Guide.

Standard mounting bolt sizes:

- a.) 3/8"-16 x 3/4" (for Type B)
- b.) 3/8"-16 x 1-3/4" (for type F, T, D and DM)
- c.) 3/8"-16 x 2-1/4" (for type D latch block)
- d.) 1/4"-20 x 5/8" (for TPS)

Tamperproof Mounting Bolts

Stainless steel (18-8) tamperproof mounting bolts are available. Button Head Socket bolts will be supplied when the letter "T" is shown in column thirteen of the interlock part number. Reference the Hybrid Ordering Guide.

Standard tamperproof mounting bolt lengths:

- a.) 3/8"-16 x 3/4" (for Type B)
- b.) 3/8"-16 x 1 3/4" (for type F, T, D and DM)
- c.) 3/8"-16 x 2 1/4" (for type D latch block)
- d.) 1/4"-20 x 3/4" (for TPS)

Tamperproof Tools

The tamperproof key tool or tamperproof bit tool are required to install the tamperproof mounting bolts.

Kirk Key Interlock Company

211 Wetmore Ave. S.E., Massillon, OH 44646

Phone: 330.833.8223 • Fax: 330.833.1528

Toll Free: 1.800.438.2442