

MOUNTING BOLTS & TOOLS



DESCRIPTION

Tamperproof mounting bolts are available in both the SD and HD series. The SD series bolts are made from 18-8 Stainless Steel and the HD series bolts are made from 316 Stainless Steel.

Standard tamperproof mounting bolt lengths:

- a.) 3/8"-16 x 3/4" (for Type B and unhousing SKRU)
- b.) 3/8"-16 x 1-3/4" (for Type F, T, D and DM)
- c.) 3/8"-16 x 2-1/4" (for Type D Latch Block & Type U lock)
- d.) 1/4"-20 x 3/4" (for Type FN & PPS)
- e.) 1/4"-20 x 2" (for Type NT)

A **tamperproof key tool or tamperproof bit tool** is required to install the tamperproof mounting bolts.

ORDER INFORMATION



TAMPERPROOF

To order with interlock: place the letter "T" in the appropriate column of the interlock part number.

To order separately: reference the bolt length desired with BU following the bolt length indicating 'Button Head/Tamperproof'.



TAMPERPROOF TOOLS

To order these tools with your tamperproof mounting bolts, please order by the specific part number listed below.

Part number 3/8" Bolt Key

2	1	H	K	H	K	A
---	---	---	---	---	---	---

Part number 1/4" Bolt Key

1	5	H	K	H	K	A
---	---	---	---	---	---	---

Part number 3/8" Bolt Bit

2	1	H	K	K	B
---	---	---	---	---	---

Part number 1/4" Bolt Bit

1	5	H	K	H	B
---	---	---	---	---	---

CONTACT INFORMATION

The Kirk Key Interlock Company LLC

9048 Meridian Circle NW North Canton, OH 44720, USA

Toll Free: +1 800-438-2442 O: +1 234-209-9301 F: +1 330-497-4400

Quotes & Inquiries sales@kirkkey.com PO Submission & Orders orders@kirkkey.com