

MOUNTING BOLTS & TOOLS



DESCRIPTION

Tamperproof mounting bolts are made from 18-8 Stainless Steel. A tamperproof key tool or tamperproof bit tool is required to install the tamperproof mounting bolts and must be ordered separately.

- Standard tamperproof mounting bolt lengths:
- a.) 3/8"-16 x 3/4" (for Type B and unhoued SKRU)
 - b.) 3/8"-16 x 1-3/4" (for Type F, T, D and DM)
 - c.) 3/8"-16 x 2-1/4" (for Type D Latch Block & Type U lock)
 - d.) 1/4"-20 x 3/4" (for Type FN & PPS)
 - e.) 1/4"-20 x 2" (for Type NT)

ORDER INFORMATION



TAMPERPROOF

To order with interlock: place the letter "T" in the appropriate column of the interlock part number.

To order separately: reference the bolt length desired with BU following the bolt length indicating 'Tamperproof'.

To order these tools with your tamperproof mounting bolts, please order by the specific part number listed below.



TAMPERPROOF TOOLS

Part number 3/8" Bolt Key	2	1	H	K	H	K	A
Part number 1/4" Bolt Key	1	5	H	K	H	K	A
Part number 3/8" Bolt Bit	2	1	H	K	H	B	
Part number 1/4" Bolt Bit	1	5	H	K	H	B	

MOUNTING BOLTS & TOOLS



TAMPERPROOF

To order with interlock: place the letter "T" in the appropriate column of the interlock part number.

To order separately: reference the bolt length desired with BU following the bolt length indicating 'Button Head/Tamperproof'.



TAMPERPROOFTOOLS

To order these tools with your tamperproof mounting bolts, please order by the specific part number listed below.

Part number 3/8" Bolt Key

2	1	H	K	H	K	A
---	---	---	---	---	---	---

Part number 1/4" Bolt Key

1	5	H	K	H	K	A
---	---	---	---	---	---	---

Part number 3/8" Bolt Bit

2	1	H	K	H	B
---	---	---	---	---	---

Part number 1/4" Bolt Bit

1	5	H	K	H	B
---	---	---	---	---	---

CONTACT INFORMATION

The Kirk Key Interlock Company LLC

9048 Meridian Circle NW North Canton, OH 44720, USA

Toll Free: +1 800-438-2442 O: +1 234-209-9301 F: +1 330-497-4400

Quotes & Inquiries sales@kirkkey.com PO Submission & Orders orders@kirkkey.com